

bond it

Never compromise on quality!



PC400 FLUSHCHEM

Heavy Duty Flushing Solution for Domestic Central Heating Systems



PLUMBERS COMPLETE RANGE

Description:

A heavy duty chemical blend for deep cleaning of central heating systems.

Application

Filling the system: Open systems should be dosed via the filling and expansion tank. Sealed systems i.e. combi, should be filled via the filling loop or a partially drained radiator.

Once system is dosed circulate the liquid through the system at normal operating temperature with all valves open and pump turned to maximum speed for at least one hour or until satisfactory performance is achieved - maximum time 4 weeks (if aluminium parts are involved - maximum 3 hours).

Once the system is performing satisfactorily turn off the boiler and drain down the system. Flush through until water runs clear. On re-filling the system use PC100 or 200 INHIBITOR.

Dosage: For optimum cleaning the system should be dosed @ 1% of system i.e. 1L of PC400 to 100L of water in system. Generally 1L is sufficient for a typical system with a 14.5Kw Boiler (50,000 Btu/hr). A badly contaminated system, larger than this will need 2% solution or dosing pro rata.

Please note: this product will not clear a completely blocked pipe.

This product is suitable for use with power flushing machines.

Limitations

DO NOT ADD TO PRIMATIC SYSTEM.

Container Size

1L plastic bottle.

Colour

Clear.

Shelf Life

12 months from date of manufacture when stored in original, sealed containers.

Storage Conditions

Store in cool, dry conditions in tightly sealed container. Do not allow to freeze.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and remove any containers to a central disposal point in accordance with local regulations.

Health & Safety

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.

Specification Summary

Appearance	Colourless liquid
Odour	Mild
Flashpoint	Non-flammable
Specific Gravity	1.06 g/sm ³
pH	11.0 - 12.0
UFI	29A0-20H4-M00K-FPNT

Product Details:

Code:	BDPC400
Colour:	Colourless
Size:	1L
Barcode:	5060021367471



Part of the Bond It Plumbers Complete Range

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position.

Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number:
6152
ISO 9001; ISO 14001;
ISO 45001



SCAN ME AND GET THE BOND IT App

BOND IT
 Head Office: Unit G16 River Bank Way, Lowfields Business Park,
 Elland, West Yorkshire HX5 9DN.
 Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
 Email: salesuk@bonditgroup.com Website: www.bonditgroup.com



V4 25/04/22
 Supercedes: V3 03/12/12